

Structural Stud (s)



MATERIAL

Web (in)	6
Flange (in)	2
Lip (in)	0.625
Yield Strength F_y (KSI)	50
Tensile Strength F_u (KSI)	65
Design Thickness (in)	0.0713
Minimum Thickness (mil)	68
Gauge	14
Available Finish G60, G90	

GROSS SECTION PROPERTIES

Weight of Member: (lb/ft)	2.60
Cross Sectional Area: A (in ²)	0.764
Moment of Inertia: I_x (in ⁴)	4.102
Section Modulus: S_x (in ³)	1.367
Radius of Gyration: R_x (in)	2.316
Moment of Inertia: I_y (in ⁴)	0.400
Radius of Gyration: R_y (in)	0.723

EFFECTIVE SECTION PROPERTIES

Moment of Inertia-Deflection: I_{xe} (in ⁴)	4.101
Section Modulus: S_{xe} (in ³)	1.332
Local Buckling Allowable Moment: M_{al} (in-k)	39.86
Distortional Buckling Allowable Moment: M_{ad} (in-k)	35.48
Allowable strong axis shear away from punch: V_{ag} (lb)	5352
Allowable strong axis shear at punch: V_{anet} (lb)	2880
(check web crippling)	

TORSIONAL SECTION PROPERTIES


St. Venant Torsional Constant: J_{x1000} (in ⁴)	1.295
Torsional Warping Constant: C_w (in ⁶)	3.047
Shear Center to Centroid on Principal X-axis: X_o (in)	-1.415
Radius of Gyration on the Centroid Principal axis: R_o (in)	2.809

PRODUCT ID

600S 200-68 (6x2x14ga) (Grade 50)

CODES & STANDARDS

- ASTM A 1003, A 653, & C 955
- AISI S100-16



See Hermes/Hephaistos Technical Manual
for complete design data