


Tracks (T)



MATERIAL	
Web (in)	2½
Flange (in)	1½
Yield Strength Fy (KSI)	33
Tensile Strength Fu (KSI)	45
Design Thickness (in)	0.0283
Minimum Thickness (mil)	27
Gauge	22
Available Finish G60, G90	

GROSS SECTION PROPERTIES	
Weight of Member: (lb/ft)	0.53
Cross Sectional Area: A (in ²)	0.156
Moment of Inertia: Ix (in ⁴)	0.181
Section Modulus: Sx (in ³)	0.137
Radius of Gyration: Rx (in)	1.078
Moment of Inertia: Iy (in ⁴)	0.037
Radius of Gyration: Ry (in)	0.486

EFFECTIVE SECTION PROPERTIES	
Moment of Inertia-Deflection: Ixe (in ⁴)	0.139
Section Modulus: Sxe (in ³)	0.082
Allowable Bending Moment: Ma (in-k)	1.61
Allowable Shear Force: Va (lb)	685
(check web crippling)	


TORSIONAL SECTION PROPERTIES	
St. Venant Torsional Constant: Jx1000 (in ⁴)	0.042
Torsional Warping Constant: Cw (in ⁶)	0.044
Shear Center to Centroid on Principal X-axis: Xo (in)	-0.976
Radius of Gyration on the Centroid Principal axis: Ro (in)	1.534

PRODUCT ID

250T 150-27 (2½x1½x22ga) Grade 33

CODES & STANDARDS

- ASTM A 1003, A 653, & C 955
- AISI S100-16



See Hermes/Hephaistos Technical Manual
for complete design data