

Tracks (T)

MATERIAL	
Web (in)	6
Flange (in)	1½
Yield Strength Fy (KSI)	33
Tensile Strength Fu (KSI)	45
Design Thickness (in)	0.0312
Minimum Thickness (mil)	30
Gauge	20D
Available Finish G60, G90	

GROSS SECTION PROPERTIES	
Weight of Member: (lb/ft)	0.96
Cross Sectional Area: A (in ²)	0.281
Moment of Inertia: Ix (in ⁴)	1.434
Section Modulus: Sx (in ³)	0.467
Radius of Gyration: Rx (in)	2.260
Moment of Inertia: Iy (in ⁴)	0.051
Radius of Gyration: Ry (in)	0.427

EFFECTIVE SECTION PROPERTIES	
Moment of Inertia-Deflection: Ixe (in ⁴)	1.159
Section Modulus: Sxe (in ³)	0.254
Allowable Bending Moment: Ma (in-k)	5.01
Allowable Shear Force: Va (lb)	456
(check web crippling)	

TORSIONAL SECTION PROPERTIES	
St. Venant Torsional Constant: Jx1000 (in ⁴)	0.091
Torsional Warping Constant: Cw (in ⁶)	0.352
Shear Center to Centroid on Principal X-axis: Xo (in)	-0.685
Radius of Gyration on the Centroid Principal axis: Ro (in)	2.400




PRODUCT ID

600T150-30 (6x1½x20Dga) Grade 33

CODES & STANDARDS

- ASTM A 1003, A 653, & C 955
- AISI S100-16



See Hermes/Hephaistos Technical Manual
for complete design data