

Tracks (T)

MATERIAL	
Web (in)	8
Flange (in)	2
Yield Strength Fy (KSI)	33
Tensile Strength Fu (KSI)	45
Design Thickness (in)	0.0346
Minimum Thickness (mil)	33
Gauge	20S
Available Finish G60, G90	

GROSS SECTION PROPERTIES	
Weight of Member: (lb/ft)	1.41
Cross Sectional Area: A (in ²)	0.415
Moment of Inertia: Ix (in ⁴)	3.750
Section Modulus: Sx (in ³)	0.921
Radius of Gyration: Rx (in)	3.006
Moment of Inertia: Iy (in ⁴)	0.135
Radius of Gyration: Ry (in)	0.571

EFFECTIVE SECTION PROPERTIES	
Moment of Inertia-Deflection: Ixe (in ⁴)	2.788
Section Modulus: Sxe (in ³)	0.424
Allowable Bending Moment: Ma (in-k)	6.99
Allowable Shear Force: Va (lb)	465
(check web crippling)	

TORSIONAL SECTION PROPERTIES	
St. Venant Torsional Constant: Jx1000 (in ⁴)	0.166
Torsional Warping Constant: Cw (in ⁶)	1.638
Shear Center to Centroid on Principal X-axis: Xo (in)	-0.917
Radius of Gyration on the Centroid Principal axis: Ro (in)	3.194




PRODUCT ID

800T200-33 (8x2x20Sga) Grade 33

CODES & STANDARDS

- ASTM A 1003, A 653, & C 955
- AISI S100-16



See Hermes/Hephaistos Technical Manual
for complete design data